



NV900

SPECIFICATIONS



Designed for continuous air disinfection and odor control in medium indoor spaces, the Novaerus Protect 900 (NV900) uses patented filter-free ultra-low energy plasma technology with a 2-speed fan. Can be wall-mounted or placed on a stand and plugs into any outlet.

MODEL

NOVAERUS NV900

Wall mountable, countertop or stand-alone unit supplied with 6.5ft power cord

ELECTRICAL RATING

120 VAC, 60 Hz, 1.07 A

Fuse Rated at 250 VAC, 3 Amps, Listed
Power consumption maximum 20 Watts

CONSTRUCTION + COLOR

Precision-cut fabricated metal casing in a white anti-bacterial powder coat finish

DIMENSIONS + WEIGHT

14.4"(w) × 14.4"(h) × 4.5"(d)
10.4 lbs

ELECTRICAL CONNECTION

Switched and fused with a grounded, molded power cord

FAN AIR FLOW VOLUME

Speed I = 150 CFM

Speed II = 180 CFM

NOISE LEVEL

Speed I = 40 dB

Speed II = 45 dB

OPERATING CONDITIONS

50°F-95°F, 10-75% Relative Humidity

SHIPPING / STORAGE CONDITIONS

41°F-122°F, Maximum 95% Relative Humidity

QUALITY & SAFETY

Manufactured under ISO 9001, ISO 14001 & OHSAS 18001

CONFORMS to the Medical Device Directive MDD 93/42/EEC

This Product meets the safety requirements of ISO61010 and UL867 Safety for Electrostatic Air Cleaners.

